

## AUTHOR INDEX

- Aizawa, M., 79  
 Auerbach, A., 195  
  
 Bergveld, P., 251  
 Boucher, J., 365  
 Boyer, A., 131  
  
 Chandler, G. K., 223  
 Charles, E., 131  
 Chiba, T., 79  
 Ciureanu, P., 229  
 Colin, Y., 263  
 Coursant, R. H., 351  
  
 Danielsson, B., 139  
 Demarne, V., 301  
 Doersam, D., 195  
 Dong-Bai Ye, 315  
  
 Eddowes, M. J., 223  
 Eyraud, L., 351  
 Eyraud, P., 351  
  
 Fink, M., 351  
 Fukumoto, H., 243  
  
 Ghers, M., 263  
 Graf, H.-J., 159  
 Grisel, A., 301  
 Groubert, E., 131  
 Guyader, J., 263  
  
 Haruta, M., 339  
 Hirata, M., 63  
 Homma, Y., 71  
 Huang, P. H., 329  
  
 Igarashi, I., 53  
 Ito, N., 165  
  
 Kamimura, K., 71  
 Kimura, J., 165  
 Kittilsland, G., 203  
 Kobayashi, A., 29  
 Kobayashi, T., 339  
 Kodato, S., 11  
 Koike, R., 11  
 Korony, G., 229  
 Kuriyama, T., 165  
 Kurobe, T., 323  
  
 Lalevic, B., 275  
 Lambrechts, M., 287  
 Laurent, Y., 263  
 Lescure, M., 365  
 Lübbbers, D. W., 159  
 Lundström, I., 139  
  
 Mehregany, M., 375  
 Mitsui, S., 147  
 Morrison, S. Roy, 89  
 Mosbach, K., 139  
 Murakami, K., 315  
  
 Nakamoto, S., 165  
 Nakane, M., 339  
 Narayanaswamy, R., 293  
  
 Onuma, Y., 71  
 Opitz, N., 159  
 Ohta, Y., 323  
 Oyabu, T., 323  
  
 Paszczynski, S., 287  
 Pedersen, K., 203  
 Pietrucha, B., 275  
 Pribat, D., 173  
  
 Rossé, G., 263  
 Russell, D. A., 293  
  
 Sadaoka, Y., 147, 243  
 Sakai, Y., 147, 243  
 Sano, H., 339  
 Sansen, W., 287  
 Santiago-Aviles, J. J., 117  
 Sasaki, A., 43  
 Sears, W. M., 89  
 Senturia, S. D., 375  
 Shinohara, H., 79  
 Smela, E., 117  
 Stemme, G., 203  
 Stenberg, M., 203  
 Suls, J., 287  
 Suzuki, K., 63  
  
 Takahashi, K., 1, 3  
 Tanigawa, H., 63  
 Tellier, J. M., 351  
  
 van der Schoot, B., 251  
 van Putten, A. F. P., 103  
 Velasco, G., 173  
  
 Wenzel, S. W., 391  
 White, R. M., 391  
 Winquist, F., 139  
  
 Yamamoto, T., 315

SUBJECT INDEX

---

- Alarm detector  
  of gas leaks, 'intelligent', 323
- Anisotropic etching  
  of Si in hydrazine, 375
- Annealing  
  effects of, and geometry optimization  
    on thin magnetoresistive head, 229
- Anodic oxidation etch-stop  
  silicon diaphragm pressure sensors  
    fabricated by, 63
- Array transducers  
  characterization of modified Pb  
    titanate piezoceramics; application  
    to design of, 351
- Bioanalytical applications  
  biosensors based on thermistors and  
    semiconductors and their, 139
- Biofilms  
  silicon sensor for measurement of  
    liquid flow and thickness of fouling,  
    203
- Biosensors  
  based on thermistors and semicon-  
    ductors and their bioanalytical  
    applications, 139
- Carbon monoxide  
  gas sensor, integrated low-power thin-  
    film, on Si, 301  
  selective CO sensor using Ti-doped  
     $\alpha$ -Fe<sub>2</sub>O<sub>3</sub> with coprecipitated ultra-  
    fine particles of Au, 339
- Chemical sensing  
  coulometric sensors, application of  
    sensor-actuator system for long-  
    term stability in, 251
- Chemical species  
  optical sensors for dissolved ionic,  
    293
- Coulometric sensors  
  application of sensor-actuator system  
    for long-term stability in chemical  
    sensing, 251
- Current  
  constant voltage, constant, Wheatstone  
    bridge configuration, 103
- Dynamic sensors  
  semiconductor, 53
- Energy control  
  microionic gas sensor for pollution  
    and, in consumer market, 173
- Enzyme-immobilized membranes  
  in multibiosensors, lift-off method for  
    patterning, 165
- Enzyme-mediated  
  pH-sensitive FET devices, problems  
    of non-linear response, 223
- Enzyme microsensor  
  for glucose with electrochemically  
    synthesized enzyme-polyaniline  
    film, 79
- FET devices  
  enzyme-mediated, pH-sensitive;  
    problems of non-linear response,  
    223
- Fiber loop  
  catheter-mounted pressure trans-  
    ducer using, 195
- Fiber sensor  
  versatile twisted optical, 117
- Fluorescence quenching  
  of indicator-treated silicone rubber  
    membranes, oxygen sensor for  
    temperature range 300 to 500 K  
    based on, 159
- Gas leaks  
  'intelligent' alarm detector of, 323
- Gas sensor(s)  
  CO, integrated low-power thin-film,  
    on Si, 301  
  microionic, for pollution and energy  
    control in consumer market, 173  
  Pt hot wire, design of, 89
- Geometry optimization  
  effects of annealing and, on thin  
    magnetoresistive head, 229
- Germanium  
  oxygen ionosorption on compressed  
    semiconducting powders of Zn and  
    Ge oxynitrides, 263

- Glucose
  - enzyme microsensor for, with electrochemically synthesized enzyme-polyaniline film, 79
- Gold
  - selective CO sensor using Ti-doped  $\alpha\text{-Fe}_2\text{O}_3$  with coprecipitated ultrafine particles of, 339
- Halogenated polymeric humidity sensors, 329
- High-voltage line
  - remote control for overhead, 365
- Humidity sensitive
  - and water-resistive polymeric materials, 243
- Humidity sensor(s)
  - halogenated polymeric, 329
  - using Zr phosphates and silicates; improvements of humidity sensitivity, 147
- Hydrazine
  - anisotropic etching of Si in, 375
- Hydrocarbon gases
  - detection of, using Pd-MNOS capacitors, 275
- Hydrogen leak detector
  - integrated, with tunnel MIS structure, 315
- Ionic chemical species
  - optical sensors for dissolved, 293
- Iron
  - selective CO sensor using Ti-doped  $\alpha\text{-Fe}_2\text{O}_3$  with coprecipitated ultrafine particles of Au, 339
- Laser powers
  - thin-film thermopiles for measuring high, 131
- Lead
  - characterization of modified Pb titanate piezoceramics; application to design of array transducers, 351
- Liquid flow
  - silicon sensor for measurement of, and thickness of fouling biofilms, 203
- Magnetoresistive head
  - effects of annealing and geometry optimization on thin, 229
- Measurement
  - and sensors, 29
- Microionic gas sensor
  - for pollution and energy control in consumer market, 173
- Microsensor
  - enzyme, for glucose with electrochemically synthesized enzyme-polyaniline film, 79
- MIS structure
  - integrated H leak detector with tunnel, 315
- MNOS capacitors
  - Pd-, detection of hydrocarbon gases using, 275
- Multibiosensors
  - lift-off method for patterning enzyme-immobilized membranes in, 165
- Optical fiber sensor
  - versatile twisted, 117
- Optical sensing devices
  - and functional, 43
- Optical sensors
  - for dissolved ionic chemical species, 293
- Oxygen inosorption
  - on compressed semiconducting powders of Zn and Ge oxynitrides, 263
- Oxygen sensor
  - for temperature range 300 to 500 K based on fluorescence quenching of indicator-treated silicone rubber membranes, 159
- Pd-MNOS capacitors
  - detection of hydrocarbon gases using, 275
- pH-sensitive
  - enzyme-mediated, FET devices; problems of non-linear response, 223
- Piezoceramics
  - characterization of modified Pb titanate; application to design of array transducers, 351
- Piezoresistive elements
  - of polycrystalline semiconductor thin films, 71
- Platinum
  - hot wire gas sensors, design of, 89
- Pollution
  - microionic gas sensor for, and energy control in consumer market, 173
- Polyaniline
  - enzyme-, film, electrochemically

- synthesized, enzyme microsensor for glucose with, 79
- Polymeric materials
  - humidity-sensitive and water-resistive, 243
- Pressure sensors
  - silicon diaphragm, fabricated by anodic oxidation etch-stop, 63
- Pressure transducer
  - catheter-mounted, using fiber loop, 195
- Remote control
  - for overhead high-voltage line, 365
- Ruthenium dioxide
  - thick-film voltammetric sensors based on, 287
- Semiconducting powders
  - of Zn and Ge oxynitrides, oxygen ionosorption on compressed, 263
- Semiconductor(s)
  - biosensors based on thermistors and, and their bioanalytical application 139
  - dynamic sensors, 53
  - thin films, piezoresistive elements of polycrystalline, 71
  - wafer alignment, inexpensive and accurate two-sided, 391
- Sensing devices
  - optical and functional, 43
- Sensor-actuator system
  - for long-term stability in chemical sensing; coulometric sensor, application of, 251
- Sensor materials
  - for the future; intelligent materials, 3
- Silicon
  - anisotropic etching of, in hydrazine, 375
  - integrated low-power thin-film CO gas sensor on, 301
- Silicon diaphragm
  - pressure sensors fabricated by anodic oxidation etch-stop, 63
- Silicon films
  - use of amorphous, as sensors, 11
- Silicon sensor
  - for measurement of liquid flow and thickness of fouling biofilms, 203
- Silicone rubber membranes
  - oxygen sensor for temperature range 300 to 500 K based on fluorescence quenching of indicator-treated, 159
- Thermistors
  - biosensors based on, and semiconductors and their bioanalytical applications, 139
- Thermopiles
  - thin-film, for measuring high laser powers, 131
- Titanium
  - selective CO sensor using Ti-doped  $\alpha$ -Fe<sub>2</sub>O<sub>3</sub> with coprecipitated ultra-fine particles of Au, 339
- Transducer
  - catheter-mounted pressure, using fiber loop, 195
- Voltage
  - constant, constant current Wheatstone bridge configuration, 103
- Voltammetric sensors
  - thick-film, based on Ru dioxide, 287
- Wafer alignment
  - semiconductor, inexpensive and accurate two-sided, 391
- Water resistive
  - humidity sensitive and, polymeric materials, 243
- Wheatstone bridge configuration
  - constant voltage constant current, 103
- Zinc
  - oxygen ionosorption on compressed semiconducting powders of Zn and Ge oxynitrides, 263
- Zirconium
  - humidity sensor using Zr phosphates and silicates; improvements of humidity sensitivity, 147

